

D.C. MILLI-OHM METER



GOM-801H



FEATURES

- * Measures from 20mΩ ~ 20kΩ in 7 Ranges
- * 1A High Test Current
- * High Resolution 10 μΩ
- * Hi/Lo Comparator Indicator and Buzz Alarm
- * 3 1/2 Digits 0.5" LED Display

GTL-108A Test Lead

For: GOM-801H/802, GDM-8255A/8251A



The GOM-801H milliohm meter is the ideal device for quick and precise component and material resistance measurements. The main display is equipped with a 3 1/2 digit 0.5" red LED with comparator indicators. Measurable objects can cover cable joints, earth bonds, switches, motors, transformers and generators. The front panel features seven selectable test ranges, 20mΩ to 20kΩ. The internal comparator is fully adjustable for the user settable Hi/Lo comparison indicator. The GOM-801H is the best choice for an inexpensive, easy to use, yet reliable milliohm meter.

SPECIFICATIONS

TEST RANGE

20, 200m , 2, 20, 200 , 2k, 20k ,
7 Ranges

TEST CURRENT (Test Voltage 0.2V)

20m /200m : 1A
2 : 0.1A
20 : 10mA
200 : 1mA
2k : 100μA
20k : 10μA

ACCURACY

Measuring 20m ± (0.2% rdg + 6 digits)
200m ~ 20k ± (0.2% rdg + 4 digits)
Setting ± (0.2% + 6 digits)

RESOLUTION

0.01 , 0.1 , 1 , 10 , (≥ symbol) 100m , 1 , 10

COMPARATOR

HI, LO settable

DISPLAY

3 1/2 digits 0.5" LED display
HI, GO, LO indicator

POWER SOURCE

AC 100V/120V/220V/230V±10% , 50/60Hz

DIMENSIONS & WEIGHT

230(W) x 95(H)x280(D)mm, Approx. 2 kg

ORDERING INFORMATION

GOM-801H High Precision Programmable DC Milli-Ohm Meter

ACCESSORIES :

User manual x 1 , Power cord x 1
Test Lead GTL-108A x 1